



prolong

TIRE CONDITIONER

HEAVY-DUTY TRUCK HIGH SPEED APPLICATION

8 OZ. (240mL)

9-22.5

16 - 20 OZ. (475mL - 600mL)

10-22.5, 11-22.5, 11-24.5, 18-19.5,

12.5-22.5, 15-22.5

1 LITRE

18-22.5, 16.5-22.5

8 LITRES

12.00x24, 13.00x24-25, 14.00x24,

16.00x24, 20.00x24, 14.00x25,

15.5x25, 16.00x25, 17.5x25

12 LITRES

20.05x25, 21.00x25, 23.5x25,

25.65x25, 29.5x25, 18.00x25,

20x30.5, 21.00x49, 24.00x49

OFF THE ROAD LOW SPEED APPLICATION

16 LITRES

16.9x28, 29.5x29, 30.65x29,

33.25x29, 18.00x33, 33.5x33,

21.00x35, 20.00x39.5, 23x41.5,

18.9x49, 24.00x49, 27x56.5

20 LITRES

26.5x29, 35-65x33, 37.5x33,

24.00x35, 29.5x35, 33.25x35,

37.25x35, 27.00x41.4, 30x41.5,

33x41.5, 21.00x49, 27x49, 30x56.5

24 LITRES

37.5x39, 40-65x39, 40.5-75x39,

24.00x43, 45-65x45, 38x46.5,

40x46.5, 45x52.5

32 LITRES

30.00x51, 33.00x51, 36.00x51,

37.5x51, 50-65x51, 33x39.5, 36x59.5,

38x59.5, 39x59.5, 50x59.2

40 LITRES

40.00x57, 37.00x57, 44x66.5

WILL NOT CORRODE MAGNESIUM OR ALUMINUM WHEELS.



3703 Mitchelmore Ave, Saskatoon, SK S7P 0C5
(306) 244-4999 info@sealcorp.ca
sealcorp.ca

SEVERE SERVICE APPLICATIONS
MAY REQUIRE AN ADDITIONAL 10%
TO SPECIFIED VOLUMES ABOVE

DO NOT STORE IN OPEN CONTAINER. WARNING: DO NOT TAKE INTERNALLY. IF SWALLOWED, DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION. KEEP OUT OF REACH OF CHILDREN